

**DIESEL GENRETOR SET ,50HZ.,400/230V.,415/240V.,1500RPM  
TP. SERIES -- PERKINS 22 - 2500 kVA.**

Model	PERKINS	Standby		Prime		Max Curr. (A)
		KVA.	KW	KVA.	KW	
TP22	404A-22G1	22	18	20	16	32
TP33	1103A-33	33	26	30	24	48
TP50	1103A-33TG1	50	40	45	36	73
TP66	1103A-33TG2	66	53	60	48	96
TP88	1104A-44TG2	88	70	80	64	127
TP110	1104C-44TAG2	110	88	100	80	159
TP150	1106A-70TG1	150	120	135	108	217
TP165	1106A-70TAG2	165	132	150	120	239
TP200	1106A-70TAG3	200	160	180	144	289
TP220	1106A-70TAG4	220	176	200	160	318
TP250	1206A-E70TTAG2	250	200	230	184	361
TP275	1206A-E70TTAG3	275	220	250	200	397
TP330	1706A-E93TAG1	339	271	307	246	489
TP400	2206C-E13TAG2	400	320	350	280	577
TP450	2206C-E13TAG3	450	360	400	320	650
TP500	2506C-E15TAG1	500	400	454	360	722
TP550	2506C-E15TAG2	550	440	500	400	794
TP660	2806C-E18TAG1A	650	520	591	473	938
TP700	2806A-E18TAG2	700	560	650	520	1011
TP825	4006-23TAG2A	820	656	746	597	1184
TP880	4006-23TAG3A	900	718	800	641	1299
TP1000	4008TAG1A	1000	800	900	720	1443
TP1100	4008TAG2	1100	800	1000	800	1587
TP1375	4012-46TWG2A	1345	1076	1250	1000	1941
TP1500	4012-46TWG3A	1500	1200	1350	1100	2165
TP1650	4012-46TAG2A	1650	1320	1500	1200	2382
TP1875	4012-46TAG3A	1873	1498	1710	1350	2703
TP2000	4016TAG1A	2000	1600	1850	1480	2887
TP2250	4016TAG2A	2250	1800	2000	1600	3248
TP2500	4016-61TRG3	2500	2000	2250	1800	3609

**REMARK**

**Standby Power:** Standby duty-operation under variable charge 500h/year with overcharge-for continuous use, derated 10 %

**Prime Power:** Continuous duty 24/24 H under variable load-10% overcharge acceptable 1h/12h