

DIESEL GENRETOR SET ,50HZ.,400/230V.,415/240V.,1500RPM

TC. SERIES -- CUMMINS 30 - 1873 kVA.

Model	CUMMINS	Standby		Prime		Max Curr. (A)
		KVA.	KW	KVA.	KW	
TC30	4B3.9-G2	30	24	27	22	43
TC44	4BT3.9-G2	44	35	40	32	63
TC62	4BTA3.9-G2	62	50	56	45	89
TC70	4BTA3.9-G2	70	56	65	52	101
TC90	4BTA3.9-G11	90	72	80	64	129
TC105	4BTA3.9-G13	105	84	95	76	152
TC100	6BT5.9-G2	103	82	94	75	148
TC115	6BT5.9-G2	115	92	105	84	165
TC125	6BTA5.9-G2	125	100	115	92	180
TC145	6BTAA5.9-G2	145	116	135	108	209
TC165	6BTAA5.9-G12	165	132	150	120	238
TC175	6CTA8.3-G2	175	140	160	128	252
TC200	6CTA8.3-G2	200	160	180	145	288
TC220	6CTAA8.3-G2	215	172	200	160	310
TC265	6LTAA8.9-G2	264	211	250	200	381
TC275	6LTAA8.9-G3	275	220	250	200	396
TC315	NTA855-G1A	313	250	275	220	451
TC350	NTA855-G1B	340	272	310	248	490
TC375	NTA855-G2A	375	300	344	275	541
TC385	NTA855-G4	388	310	350	280	560
TC410	NTAA855-G7	413	330	375	300	596
TC450	NTAA855-G7A	450	360	N/A	N/A	649
TC500	KTA19-G3	500	400	450	360	721
TC550	KTA19-G3A	563	450	500	400	812
TC550	KTA19-G4	563	450	500	400	812
TC550	KTAA19-G5	590	472	525	420	851
TC625	KTAA19-G5	631	505	525	420	911
TC650	KTAA19-G6	650	520	575	460	938
TC690	KTAA19-G6A	688	550	N/A	N/A	993
TC800	KT38-GA	800	640	725	580	1154
TC825	KTA38-G2	825	660	750	600	1191
TC880	KTA38-G2B	888	710	800	640	1271
TC1000	KTA38-G2A	1000	800	910	728	1444
TC1100	KTA38-G5	1100	880	1000	800	1588
TC1250	KTA38-G9	1230	984	N/A	N/A	1776
TC1375	KTA50-G3	1345	1076	1250	1000	1942
TC1650	KTA50-G8	1650	1320	1375	1100	2382
TC1650	KTA50-GS8	1650	1320	1475	1180	2382
TC1875	KTA50-G15	1873	1498	1675	1340	2704

REMARK

Standby Power: Standby duty-operation under variable charge 500h/year with overcharge-for continuous use, derated 10 %

Prime Power: Continuous duty 24/24 H under variable load-10% overcharge acceptable 1h/12h